



FEATURES

- Patented rotating coil system – coil rotates with the arm and flask keeping the metal in liquid phase during the injection
- Built in vacuum pump and Argon gas circuit with programmable vacuum/argon washing cycles
- Built-in Infrared pyrometer with temperature control
- Fully automatic or manual control of the casting process
- Modern digital controls with self diagnostic features
- Multiple user programs with programmable parameters: power level, rotation speed, acceleration, melting temperature, holding time
- Internal water cooling system. Optional external chiller for continuous operation

The SuperCast Pro systems have been developed specifically for sample preparation and QC testing in research, recycling, foundry or metallurgical facilities.

Utilizing latest high frequency induction heating technology, capable of melting all metals and alloys (precious and non-precious) in ingot or powder form.

Patented RCS (Rotating Coil System) ensures producing samples with excellent repeatability and quality.

Very high melting efficiency and speed, capable of producing up to 12 casting samples per hour in 24 hour operation.

Compact, reliable systems with integrated vacuum pump and water cooling. Easy to install, operate and maintain.

CE certified with integrated safety and protection features.

APPLICATIONS


Spectroscopy, XRF and RFA sample preparation, re-melting, fusion of metal alloys and powders, casting of AAS, ICP, X-Emission samples, metallurgical research, Titanium and special metals casting

HEADQUARTERS

10 Colt Court
Ronkonkoma, New York 11779
Tel: 631.467.6814
sales@ultraflexpower.com



ultraflexpower.com



BENEFITS

- Improved energy efficiency compared to resistance or flame heating
- High degree of controllability, repeatability and quality of samples
- Increased productivity by rapid melting and sample casting
- Optimal mixing of the melt provided by the induction heating field
- Easy handling with operation safety at increased temperatures
- Low maintenance requirements, easy to use systems

SPECIFICATION

	SuperCast AP5/AP-T 0UPT-017-710	SuperCast A5/A5-T 0UPT-017-710
Absorbed Power kW (max)	4.4 kW	5.4 kW
Frequency kHz	350-400 kHz	85-105 kHz
AC Line Volts (50/60Hz) , 1 Phase	230±10%	230±10%
Line Phases	1	1
Crucible Capacity	10-30 ccm	10-30 ccm
Type of material	Powder	Small pieces
Max Melting T°	2000 C°	2000 C°
Cooling System	Water-Internal	Water-Internal
Weight Lb (kg)	155 kg (342 Lb)	175 kg (385.8 Lb)
Dimensions Inch (cm) WxDxH	25.2" x 26.4" x 41.3" (64 x 67 x 105)	25.2" x 26.4" x 41.3" (64 x 67 x 105)

HEADQUARTERS

10 Colt Court
 Ronkonkoma, New York 11779
 Tel: 631.467.6814
 sales@ultraflexpower.com



ultraflexpower.com

